Waves

2. Wave Transformation

Wave Transformation

- **Refraction**
  - change of **direction** on moving into shallower water
- **Shoaling**
  - change of **height** on moving into shallower water
- **Breaking**
  - collapse of waves after steepening
- **Diffraction**
  - spreading of waves into geometric shadow
- **Reflection**
  - reversal of direction at boundary

Wave Transformation

2. WAVE TRANSFORMATION

2.1 Refraction

2.2 Shoaling

2.3 Breaking

2.4 Diffraction

2.5 Reflection

Refraction

As waves move into shallower water:

- **period** remains constant;
- **speed** decreases (because depth decreases).

Hence:

- for oblique waves, **direction** changes.

Refraction is the change in **direction** with wave speed. For water waves, this speed change is due to a change in depth.

The change in direction is governed by **Snell's Law**.

Snell's Law

$$T = \frac{\text{distance}}{\text{speed}} = \frac{d \sin\theta_1}{c_1} = \frac{d \sin\theta_2}{c_2}$$



$$\frac{\sin\theta_1}{c_1} = \frac{\sin\theta_2}{c_2}$$

$$\frac{k_1 \sin\theta_1}{\omega_1} = \frac{k_2 \sin\theta_2}{\omega_2}$$

$$\omega_1 = \omega_2$$

$$(k \sin\theta)_1 = (k \sin\theta)_2$$

Refraction



Example

A straight coastline borders a uniformly-sloping sea bed. Regular waves are observed to cross the 8 m depth contour at an angle of 14° to the coastline-normal, with wavelength 45 m. Find:

(a) the wave period;

(b) the wavelength in deep water;

(c) the direction in deep water.

A straight coastline borders a uniformly-sloping sea bed. Regular waves are observed to cross the 8 m depth contour at an angle of 14° to the coastline-normal, with wavelength 45 m. Find:

(a) the wave period;
(b) the wavelength in deep water;
(c) the direction in deep water.

Inshore:

$$h = 8 \text{ m}$$
$$\theta = 14°$$
$$L = 45 \text{ m}$$

$$k = \frac{2\pi}{L} = 0.1396 \text{ m}^{-1}$$

$$\omega^2 = gk \tanh kh \qquad \omega = 1.051 \text{ rad s}^{-1}$$

$$T = \frac{2\pi}{\omega} = \mathbf{5.978 \text{ s}}$$

Deep water:

$$L_0 = \frac{gT^2}{2\pi} = \mathbf{55.80 \text{ m}}$$

Snell's Law:

$$(k \sin\theta)_0 = (k \sin\theta)_{8 \text{ m}} \qquad k_0 = \frac{2\pi}{L_0} = 0.1126 \text{ m}^{-1}$$

$$0.1126 \sin\theta_0 = 0.1396 \sin 14°$$

$$\boldsymbol{\theta_0 = 17.45°}$$

Wave Transformation

2. WAVE TRANSFORMATION

2.1 Refraction

2.2 Shoaling

2.3 Breaking

2.4 Diffraction

2.5 Reflection

Shoaling

If there is no energy dissipation:

- **shoreward component of power** remains constant;

or

- **power between orthogonals** is constant.



$$P \cos \theta = \text{constant}$$

Shoaling

$$P \cos\theta = \text{constant}$$

Energy: $E = \frac{1}{2}\rho g A^2 \quad = \frac{1}{8}\rho g H^2$ (per unit area)

Power: $P = E c_g \quad = (\frac{1}{8}\rho g H^2)(nc)$ (per unit length of crest)

$$(H^2 nc \cos\theta)_1 = (H^2 nc \cos\theta)_2$$

$$n = \frac{1}{2}\left[1 + \frac{2kh}{\sinh 2kh}\right]$$

$$c = \frac{\omega}{k}$$

Shoaling

$$(H^2 nc\cos\theta)_1 = (H^2 nc\cos\theta)_2$$

$$H_2 = H_1 \underbrace{\left(\frac{\cos\theta_1}{\cos\theta_2}\right)^{1/2}}_{\substack{\text{refraction}\\ \text{coefficient}\\ K_R}} \underbrace{\left(\frac{(nc)_1}{(nc)_2}\right)^{1/2}}_{\substack{\text{shoaling}\\ \text{coefficient}\\ K_S}}$$



Example

Waves propagate towards a long straight coastline that has a very gradual bed slope normal to the coast. In water depth of 20 m, regular waves propagate at heading $\theta = 40°$ relative to the bed slope.

(a) Sketch the shape of a wave ray from the 20 m depth contour to the 5 m depth contour for a wave that is of deep-water type in both depths and, separately, for a wave that is of shallow water type in both depths. Calculations are not required.

(b) For a wave with period $T = 8$ s and height 1.2 m at 20 m depth, calculate the wave heading and wave height at the 5 m depth contour.

Waves propagate towards a long straight coastline that has a very gradual bed slope normal to the coast. In water depth of 20 m, regular waves propagate at heading $\theta = 40°$ relative to the bed slope.

(a) Sketch the shape of a wave ray from the 20 m depth contour to the 5 m depth contour for a wave that is of deep-water type in both depths and, separately, for a wave that is of shallow water type in both depths. Calculations are not required.



Deep-water (or **short-wavelength**) waves, by definition, do not feel the effect of the bed. Hence they propagate undisturbed.

Shallow-water (or **long-wavelength**) waves, reduce in wavelength and slow down. Hence they bend toward the normal.

Waves propagate towards a long straight coastline that has a very gradual bed slope normal to the coast. In water depth of 20 m, regular waves propagate at heading $\theta = 40°$ relative to the bed slope.

(b) For a wave with period $T = 8$ s and height 1.2 m at 20 m depth, calculate the wave heading and wave height at the 5 m depth contour.

$T = 8\ \mathrm{s}$ (both depths)

$$\omega = \frac{2\pi}{T} = 0.7854\ \mathrm{rad\ s^{-1}}$$

Dispersion:

$$\omega^2 = gk \tanh kh$$

$$\frac{\omega^2 h}{g} = kh \tanh kh$$

$$kh = \frac{\omega^2\, h/g}{\tanh kh} \quad \text{or} \quad kh = \frac{1}{2}\left(kh + \frac{\omega^2\, h/g}{\tanh kh}\right)$$

Refraction (Snell's Law):

$$(k \sin\theta)_{5\ \mathrm{m}} = (k \sin\theta)_{20\ \mathrm{m}}$$

Shoaling:

$$(H^2 nc \cos\theta)_{5\ \mathrm{m}} = (H^2 nc \cos\theta)_{20\ \mathrm{m}}$$

Waves propagate towards a long straight coastline that has a very gradual bed slope normal to the coast. In water depth of 20 m, regular waves propagate at heading $\theta = 40°$ relative to the bed slope.

(b) For a wave with period $T = 8$ s and height 1.2 m at 20 m depth, calculate the wave heading and wave height at the 5 m depth contour.

$\omega = 0.7854 \text{ rad s}^{-1}$

	$h = 5$ m	$h = 20$ m
$\omega^2 h/g$	0.3144	1.258
Iteration:	$kh = \frac{1}{2}\left(kh + \frac{0.3144}{\tanh kh}\right)$	$kh = \frac{1.258}{\tanh kh}$
kh	0.5918	1.416
k	0.1184 m^{-1}	0.07080 m^{-1}
$c = \frac{\omega}{k}$	6.633 m s^{-1}	11.09 m s^{-1}
$n = \frac{1}{2}\left[1 + \frac{2kh}{\sinh 2kh}\right]$	0.8999	0.6674
θ	---	40°
H	---	1.2 m

Refraction: $(k \sin\theta)_{5\text{ m}} = (k \sin\theta)_{20\text{ m}}$

$0.1184 \sin\theta_{5\text{m}} = 0.07080 \sin 40°$ $\qquad$ $\boldsymbol{\theta_{5\text{m}} = 22.60°}$

Shoaling: $(H^2 nc \cos\theta)_{5\text{ m}} = (H^2 nc \cos\theta)_{20\text{ m}}$ $\qquad$ $\boldsymbol{H_{5\text{m}} = 1.217 \text{ m}}$

$H_{5\text{m}}^2 \times 0.8999 \times 6.633 \times \cos 22.60° = 1.2^2 \times 0.6674 \times 11.09 \times \cos 40°$

Wave Transformation

2. WAVE TRANSFORMATION

2.1 Refraction

2.2 Shoaling

2.3 Breaking

2.4 Diffraction

2.5 Reflection

Breaking – Miche Criterion

$$\left(\frac{H}{L}\right)_b = 0.14\tanh(kh)_b$$

Idea: breaking occurs when $u_{\max}/c$ exceeds a critical value

$$\frac{u_{\max}}{c} = \frac{(Agk/\omega)}{(\omega/k)} \qquad = \frac{Agk^2}{\omega^2} \qquad = \frac{Ak}{\tanh kh} \qquad = \frac{\pi\, H/L}{\tanh kh}$$

At breaking: $$\frac{H}{L} = \text{constant} \times \tanh(kh)$$

Deep water: $$\left(\frac{H}{L}\right)_b = 0.14 \approx \frac{1}{7}$$

Shallow water: $$\left(\frac{H}{L}\right)_b = 0.14 \times \frac{2\pi h}{L}$$

$$\left(\frac{H}{h}\right)_b = 0.88$$

Breaker Height Index

Breaker height index:

$$\Omega_b = \frac{H_b}{H_0} \quad \left(\frac{\text{wave height at breaking}}{\text{deep–water wave height}}\right)$$

e.g.

$$\Omega_b = 0.56\left(\frac{H_0}{L_0}\right)^{-1/5}$$

Deep-water quantities extrapolated from height and period measured at one point:

H_0 from shoaling: $(H^2 nc\cos\theta)_0 = (H^2 nc\cos\theta)_{\text{measured}}$

L_0 from: $L_0 = \dfrac{gT^2}{2\pi}$

Breaker Depth Index

Breaker depth index:

$$\gamma_b = \left(\frac{H}{h}\right)_b \qquad \left(\frac{\text{wave height at breaking}}{\text{water depth at breaking}}\right)$$

On a mild slope: $\gamma_b = 0.78$

On a beach of slope m: $\gamma_b = b - a\dfrac{H_b}{gT^2} \qquad = b - a\dfrac{H_b}{2\pi L_0}$

$$a = 43.8(1 - e^{-19m}), \qquad b = \frac{1.56}{1 + e^{-19.5m}}$$

Types of Breaker

Irribarren Number (aka **surf-similarity parameter**):

$$\left(\frac{\text{beach slope}}{\sqrt{\text{wave steepness}}}\right)$$

$$\xi_0 = \frac{m}{\sqrt{H_0/L_0}}$$

$$\xi_b = \frac{m}{\sqrt{H_b/L_0}}$$

$\xi_0 < 0.5$	spilling breakers
$0.5 < \xi_0 < 3.3$	plunging breakers
$3.3 < \xi_0$	surging or collapsing breakers

Types of Breaker



Spilling



Plunging



Collapsing



Surging

Example

Waves propagate towards a long straight coastline that has a constant bed slope of 1 in 100. Consider the *x*-axis to be normal to the coastline and the *y*-axis parallel to the coastline. Waves propagate at an angle θ to the *x*-axis.

(a) A wave with period 7 s and height 1.2 m crosses the 36 m depth contour at angle $\theta = 22°$.

   (i) Determine the direction, height and power per metre width of wave crest at the 4 m depth contour.

   (ii) Explain how height changes between these depths.

(b) A wave with period 7 s and height 1.0 m crosses the 4 m depth contour at angle $\theta = 0°$. Determine the breaking wave height and breaking depth from their corresponding indices and identify the type of breaker expected.

(c) Further along the coast, waves propagate over the outflow of a river. In water depth of 14 m, measurements indicate a period of 7 s and depth-averaged flow velocity of 0.8 m s^{-1} against the wave direction. Determine the wavelength.

Waves propagate towards a long straight coastline that has a constant bed slope of 1 in 100. Consider the *x*-axis to be normal to the coastline and the *y*-axis parallel to the coastline. Waves propagate at an angle θ to the *x*-axis.

(a) A wave with period 7 s and height 1.2 m crosses the 36 m depth contour at angle $\theta = 22°$.

(i) Determine the direction, height and power per metre width of wave crest at the 4 m depth contour.

$T = 7\ \mathrm{s}$ (both depths)

$$\omega = \frac{2\pi}{T} = 0.8976\ \mathrm{rad\ s^{-1}}$$

Dispersion:

$$\omega^2 = gk \tanh kh$$

$$\frac{\omega^2 h}{g} = kh \tanh kh$$

$$kh = \frac{\omega^2\, h/g}{\tanh kh} \qquad \text{or} \qquad kh = \frac{1}{2}\left(kh + \frac{\omega^2\, h/g}{\tanh kh}\right)$$

Refraction (Snell's Law):

$$(k \sin\theta)_{4\ \mathrm{m}} = (k \sin\theta)_{36\ \mathrm{m}}$$

Shoaling:

$$(H^2 nc \cos\theta)_{4\ \mathrm{m}} = (H^2 nc \cos\theta)_{36\ \mathrm{m}}$$

Power:

$$P = Ec_g \qquad E = \frac{1}{8}\rho g H^2 \qquad c_g = nc$$

Waves propagate towards a long straight coastline that has a constant bed slope of 1 in 100. Consider the *x*-axis to be normal to the coastline and the *y*-axis parallel to the coastline. Waves propagate at an angle θ to the *x*-axis.

(a) A wave with period 7 s and height 1.2 m crosses the 36 m depth contour at angle $\theta = 22°$.

(i) Determine the direction, height and power per metre width of wave crest at the 4 m depth contour.

$\omega = 0.8976 \text{ rad s}^{-1}$

	$h = 4$ m	$h = 36$ m
$\omega^2 h/g$	0.3285	2.957
Iteration:	$kh = \frac{1}{2}\left(kh + \frac{0.3285}{\tanh kh}\right)$	$kh = \frac{2.957}{\tanh kh}$
kh	0.6065	2.973
k	0.1516 m^{-1}	0.08258 m^{-1}
$c = \frac{\omega}{k}$	5.921 m s^{-1}	10.87 m s^{-1}
$n = \frac{1}{2}\left[1 + \frac{2kh}{\sinh 2kh}\right]$	0.8956	0.5156
θ	---	22°
H	---	1.2 m

Refraction: $(k \sin\theta)_{4\text{ m}} = (k \sin\theta)_{36\text{ m}}$

$0.1516 \sin\theta_{4\text{ m}} = 0.08258 \sin 22°$ $\qquad \boldsymbol{\theta_{4\text{m}} = 11.77°}$

Shoaling: $(H^2 nc \cos\theta)_{4\text{ m}} = (H^2 nc \cos\theta)_{36\text{ m}}$ $\qquad \boldsymbol{H_{4\text{m}} = 1.201 \text{ m}}$

$H_{4\text{ m}}^2 \times 0.8956 \times 5.921 \times \cos 11.77° = 1.2^2 \times 0.5156 \times 10.87 \times \cos 22°$

Power: $P = Ec_g = \frac{1}{8}\rho g H^2 (nc) = \mathbf{9614 \text{ W m}^{-1}}$

(b) A wave with period 7 s and height 1.0 m crosses the 4 m depth contour at angle $\theta = 0°$. Determine the breaking wave height and breaking depth from their corresponding indices and identify the type of breaker expected.

$$H_b = 0.56 H_0 \left(\frac{H_0}{L_0}\right)^{-1/5}$$

$$\gamma_b \equiv \left(\frac{H}{h}\right)_b = b - a\frac{H_b}{gT^2}$$

$$a = 43.8(1 - \mathrm{e}^{-19m})$$

$$b = \frac{1.56}{1 + \mathrm{e}^{-19.5m}}$$

$$(H^2nc)_0 = (H^2nc)_{4\,\mathrm{m}}$$

$$T = 7\ \mathrm{s}$$

Depth 4 m	Deep water
$H = 1.0\ \mathrm{m}$	?
$n = 0.8956$	$n = 0.5$
$c = 5.921\ \mathrm{m\ s^{-1}}$	$c = \frac{gT}{2\pi} = 10.93\ \mathrm{m\ s^{-1}}$
	$L_0 = \frac{gT^2}{2\pi} = \mathbf{76.50\ m}$

Shoaling:

$$(H^2nc)_0 = (H^2nc)_{4\,\mathrm{m}}$$

$$H_0^2 \times 0.5 \times 10.93 = 1 \times 0.8956 \times 5.921$$

$$\boldsymbol{H_0 = 0.9851\ \mathrm{m}}$$

(b) A wave with period 7 s and height 1.0 m crosses the 4 m depth contour at angle $\theta = 0°$. Determine the breaking wave height and breaking depth from their corresponding indices and identify the type of breaker expected.

$$H_b = 0.56 H_0 \left(\frac{H_0}{L_0}\right)^{-1/5}$$

$$\gamma_b \equiv \left(\frac{H}{h}\right)_b = b - a\frac{H_b}{gT^2}$$

$$a = 43.8(1 - \mathrm{e}^{-19m})$$

$$b = \frac{1.56}{1 + \mathrm{e}^{-19.5m}}$$

$T = 7$ s $\quad H_0 = 0.9851$ m $\quad m = 0.01$

$L_0 = 76.50$ m

Breaking height:

$$\boldsymbol{H_b = 1.317 \text{ m}}$$

Breaking depth:

$a = 7.579$

$b = 0.8558$

$\gamma_b = 0.8350$

$$\boldsymbol{h_b = 1.577 \text{ m}}$$

Breaker type:

$$\xi_0 = \frac{m}{\sqrt{H_0/L_0}} = \mathbf{0.0881}$$

spilling breakers

(c) Further along the coast, waves propagate over the outflow of a river. In water depth of 14 m, measurements indicate a period of 7 s and depth-averaged flow velocity of 0.8 m s^{-1} against the wave direction. Determine the wavelength.

$$h = 14 \text{ m}$$

$$T_a = 7 \text{ s}$$

$$U = -0.8 \text{ m s}^{-1}$$

$$\omega_a = \frac{2\pi}{T_a} = 0.8976 \text{ rad s}^{-1}$$

$$(\omega_a - kU)^2 = \omega_r^2 = gk \tanh kh$$

$$k = \frac{(\omega_a - kU)^2}{g \tanh kh}$$

$$k = \frac{(0.8976 + 0.8k)^2}{9.81 \tanh 14k}$$

$$k = 0.1087 \text{ m}^{-1}$$

$$L = \frac{2\pi}{k} = \mathbf{57.80 \text{ m}}$$

Example

Waves propagate towards a straight shoreline. The wave heading is equal to the angle formed between wave crests and the bed contours. The bed slope is less than 1 in 100. Waves are measured in 30 m depth and wave conditions at 6 m depth are required to inform design of nearshore structures.

Regular waves are measured with period of 7 s and height of 3 m.

(a) Determine the water depth in which waves with this period can be considered as deep-water waves.

(b) For 30 m depth, determine the breaking height by the Miche criterion and briefly describe this type of breaking wave.

(c) If the heading is zero degrees, calculate wave height in 6 m depth. State your assumptions.

(d) If the heading of the measured conditions is 30°, calculate the wave heading and height in 6 m depth. Hence calculate the change of wave power per unit width of wave crest (kW m^{-1}) between the two depths.

Waves propagate towards a straight shoreline. The wave heading is equal to the angle formed between wave crests and the bed contours. The bed slope is less than 1 in 100. Waves are measured in 30 m depth and wave conditions at 6 m depth are required to inform design of nearshore structures.

Regular waves are measured with period of 7 s and height of 3 m.

(a) Determine the water depth in which waves with this period can be considered as deep-water waves.

$$T = 7 \text{ s}$$

$$\omega = \frac{2\pi}{T} \quad = 0.8976 \text{ rad s}^{-1}$$

$$\omega^2 = gk \tanh kh$$

$$\frac{\omega^2 h}{g} = kh \tanh kh$$

Deep-water waves if $kh > \pi$:

$$0.08213h > \pi \tanh \pi$$

$$\boldsymbol{h > 38.11 \text{ m}}$$

(b) For 30 m depth, determine the breaking height by the Miche criterion and briefly describe this type of breaking wave.

$$\omega = 0.8976 \text{ rad s}^{-1}$$

$$h = 30 \text{ m}$$

Miche criterion: $$\frac{H_b}{L} = 0.14 \tanh kh$$

Irribarren number: $$\xi_b = \frac{m}{\sqrt{H_b/L_0}}$$

Dispersion relation: $$\omega^2 = gk \tanh kh$$

$$\frac{\omega^2 h}{g} = kh \tanh kh$$

$$2.464 = kh \tanh kh$$

$$kh = \frac{2.464}{\tanh kh}$$

$$kh = 2.498$$

$$k = 0.08327 \text{ m}^{-1}$$

$$L = \frac{2\pi}{k} = 75.46 \text{ m}$$

Miche criterion:

$$\frac{H_b}{75.46} = 0.14 \tanh 2.498$$

$$\boldsymbol{H_b = 10.42 \text{ m}}$$

$$L_0 = \frac{gT^2}{2\pi} = 76.50 \text{ m}$$

$$m < 0.01$$

$$\xi_b < \frac{0.01}{\sqrt{10.42/76.50}} = 0.0271$$

spilling breakers

(c) If the heading is zero degrees, calculate wave height in 6 m depth. State your assumptions.

Shoaling (no refraction): $(H^2nc)_{6\,\mathrm{m}} = (H^2nc)_{30\,\mathrm{m}}$

$\omega = 0.8976\ \mathrm{rad\ s^{-1}}$ $H_{30\,\mathrm{m}} = 3\ \mathrm{m}$

	6 m depth (exercise)	30 m depth (earlier)
kh	0.7651	2.498
k	$0.1275\ \mathrm{m^{-1}}$	$0.08327\ \mathrm{m^{-1}}$
$c = \dfrac{\omega}{k}$	$7.04\ \mathrm{m\ s^{-1}}$	$10.78\ \mathrm{m\ s^{-1}}$
$n = \dfrac{1}{2}\left[1 + \dfrac{2kh}{\sinh 2kh}\right]$	0.8476	0.5338
H	---	3 m

Shoaling:

$$H_{6\,\mathrm{m}}^2 \times 0.8476 \times 7.04 = 3^2 \times 0.5338 \times 10.78$$

$$\boldsymbol{H_{6\,\mathrm{m}} = 2.946\ \mathrm{m}}$$

(d) If the heading of the measured conditions is 30°, calculate the wave heading and height in 6 m depth. Hence calculate the change of wave power per unit width of wave crest (kW m^{-1}) between the two depths.

Refraction: $(k \sin\theta)_{6\,\mathrm{m}} = (k \sin\theta)_{30\,\mathrm{m}}$

Shoaling (with refraction): $(H^2 nc \cos\theta)_{6\,\mathrm{m}} = (H^2 nc \cos\theta)_{30\,\mathrm{m}}$

$\omega = 0.8976\ \mathrm{rad\ s^{-1}}$

	6 m depth	30 m depth
kh	0.7651	2.498
k	$0.1275\ \mathrm{m^{-1}}$	$0.08327\ \mathrm{m^{-1}}$
$c = \dfrac{\omega}{k}$	$7.04\ \mathrm{m\ s^{-1}}$	$10.78\ \mathrm{m\ s^{-1}}$
$n = \dfrac{1}{2}\left[1 + \dfrac{2kh}{\sinh 2kh}\right]$	0.8476	0.5338
θ	---	30°
H	---	3 m

Refraction: $0.1275 \sin\theta_{6\,\mathrm{m}} = 0.08327 \sin 30°$ $\qquad \boldsymbol{\theta_{6\,\mathrm{m}} = 19.06°}$

Shoaling: $H_{6\,\mathrm{m}}^2 \times 0.8476 \times 7.040 \times \cos 19.06° = 3^2 \times 0.5338 \times 10.78 \times \cos 30°$

$\boldsymbol{H_{6\,\mathrm{m}} = 2.820\ \mathrm{m}}$

(d) If the heading of the measured conditions is 30°, calculate the wave heading and height in 6 m depth. Hence calculate the change of wave power per unit width of wave crest (kW m^{-1}) between the two depths.

$$P = Ec_g \qquad E = \frac{1}{8}\rho g H^2 \qquad c_g = nc$$

$$\Delta P = \left(\frac{1}{8}\rho g H^2 nc\right)_{30\ \mathrm{m}} - \left(\frac{1}{8}\rho g H^2 nc\right)_{6\ \mathrm{m}} = \mathbf{5.451\ kW\ m^{-1}}$$

Wave Transformation

2. WAVE TRANSFORMATION

2.1 Refraction

2.2 Shoaling

2.3 Breaking

2.4 Diffraction

2.5 Reflection

Diffraction

Diffraction is the spreading of waves into a region of geometric shadow.

It occurs because there cannot be discontinuities at the boundary of the illuminated zone.



Diffraction – Semi-Infinite Breakwater

diffracted wave crests



Normal incidence



Oblique incidence

incident + reflected waves

Diffraction Coefficient

$$K_D(x) = \frac{H(x)}{H_0}$$

Semi-infinite plane breakwater; 90° wave incidence



Diffraction Coefficient

Breakwater with a $2L$ gap



Offshore breakwater, length $10L$



Example

A harbour is to be protected by an L-shaped breakwater as sketched. Determine the length X of the outer arm necessary for the wave height at point P to be 0.3 m when incident waves have a height of 3 m and a period of 5 s.



The depth is everywhere uniform at 5 m. The diagram for the appropriate approach angle is shown. Neglect reflections within the harbour.



A harbour is to be protected by an L-shaped breakwater as sketched. Determine the length X of the outer arm necessary for the wave height at point P to be 0.3 m when incident waves have a height of 3 m and a period of 5 s.

The depth is everywhere uniform at 5 m. The diffraction diagram for the appropriate approach angle is shown. Neglect reflections within the harbour.

Require $K = \dfrac{0.3}{3} = 0.1$



From the diagram, this occurs at $x/L = 4.0$

The total arm length in m is $X = x + 90 \quad = 4L + 90$

A harbour is to be protected by an L-shaped breakwater as sketched. Determine the length X of the outer arm necessary for the wave height at point P to be 0.3 m when incident waves have a height of 3 m and a period of 5 s.

The depth is everywhere uniform at 5 m. The diffraction diagram for the appropriate approach angle is shown. Neglect reflections within the harbour.

$$h = 5 \text{ m}$$

Arm length $X = 4L + 90$

$$T = 5 \text{ s}$$

$$\omega = \frac{2\pi}{T} = 1.257 \text{ rad s}^{-1}$$

$$\omega^2 = gk \tanh kh$$

$$\frac{\omega^2 h}{g} = kh \tanh kh$$

$$kh \tanh kh = 0.8053$$

$$kh = \frac{0.8053}{\tanh kh} \quad \text{or} \quad kh = \frac{1}{2}\left(kh + \frac{0.8053}{\tanh kh}\right)$$

$$kh = 1.037$$

$$k = 0.2074 \text{ m}^{-1}$$

$$L = \frac{2\pi}{k} = 30.30 \text{ m}$$

Arm length $X = 211$ m

Wave Transformation

2. WAVE TRANSFORMATION

2.1 Refraction

2.2 Shoaling

2.3 Breaking

2.4 Diffraction

2.5 Reflection

Reflection

For a rigid, impermeable boundary: $u = 0$ at the boundary

Superpose two **progressive waves** moving in opposite directions:

$$\eta = A\cos(kx - \omega t) + A\cos(-kx - \omega t)$$

$$= A[\cos(kx - \omega t) + \cos(kx + \omega t)]$$

$$= 2A\cos kx \cos \omega t$$

This is a **standing wave** ... with **twice the amplitude**

... and **nodes** every half-wavelength



Reflection

$$\eta = 2A \cos kx \cos \omega t$$

$$u = \frac{2Agk}{\omega} \frac{\cosh k(h+z)}{\cosh kh} \sin kx \sin \omega t$$



- Reflection can be represented by the superposition of two equal and opposite progressive waves to form a standing wave.
- The standing wave has the same wavelength and frequency but twice the amplitude.
- There are surface nodes (i.e. zeroes of η) separated by half a wavelength, with velocity nodes intermediate between.
- The point of reflection corresponds to a point of zero velocity and double-amplitude displacement.

Seiching

Seiches are resonant standing waves set up in enclosed basins (lakes, harbours, ...)



The basin length is a whole number of half-wavelengths:

$$B = n_s\left(\tfrac{1}{2}L\right) \qquad L = \frac{2B}{n_s}$$

$$\text{period} = \frac{\text{wavelength}}{\text{speed}}$$

$$T = \frac{2B}{n_s\sqrt{gh}}$$

Reflection

Lake Baikal in Siberia contains about one fifth of the world's fresh-water resources. It is 636 km long, with an average depth of 744 m. Find the fundamental period for seiching.

Lake Baikal in Siberia contains about one fifth of the world's fresh-water resources. It is 636 km long, with an average depth of 744 m. Find the fundamental period for seiching.



Fundamental
(mode 1)

$$L = 2 \times \text{length of lake} \quad = 1.272 \times 10^6 \text{ m}$$

$$c = \sqrt{gh} \quad = 85.43 \text{ m s}^{-1}$$

$$T = \frac{L}{c} \quad = 14890 \text{ s} \qquad \mathbf{(4.1\ hours)}$$